

B	0/-1
H	± 0.2

Standard clackband


Pitch	Strip type	Article-No.
C = 65	X = 20	2G32.1000
C = 50	X = 20	2G32.1010

Tensile strength of bare tape 240 N with B = 15 mm

Pitch	Strip type	Article- No.
C = 65	X = 13	2G32.1200
C = 50	X = 13	2G32.1210

Dimensions:

C	Pitch	65 or 50
B	Band width in mm	≥ 5; max. 460
L	Band length in m	as desired; (note max. m / reel)
H	Thickness in mm	X = 20: 4, 5, 6, 7, 8 X = 13: 4, 5, 6



The clackband is supplied on reels. Please note: Max. running meters per reel as stated in the table. As standard procedure, the clackband ordered is reeled on as few reels as possible.

If this is not desired, please indicate on your order sheet the desired number of reels relative to the quantity of clackband ordered.

Running meters per reel 14 kg ea. (approximately)

Pitch	H	B 8	B 12	B 16	B 20	B 24
65	4	1120	715	525	415	345
	5	930	605	450	355	290
	6	800	525	385	310	255
	7	700	465	345	270	225
	8	620	410	305	245	200
50	4	845	570	430	315	280
	5	735	480	360	285	235
	6	635	415	310	245	205
	7	560	365	270	215	180
	8	505	325	245	190	160

Weight in grams/running meter (approximately):

Pitch	H	B 8	B 12	B 16	B 20	B 24
65	4	12.5	19.5	26.5	33.5	40.5
	5	15.0	23.0	31.0	39.0	47.5
	6	17.5	26.5	36.0	45.0	54.5
	7	20.0	30.0	40.5	51.0	61.5
	8	22.5	34.0	45.5	57.0	68.5
50	4	16.5	24.5	32.5	44.0	49.5
	5	19.0	29.0	38.5	48.5	58.5
	6	22.0	33.5	45.0	56.5	68.0
	7	25.0	38.0	51.0	64.0	77.5
	8	27.5	42.5	57.0	72.0	87.0

Running meters and weights are related to strip type X = 20.

Codes for ordering:

Examples

Article No.	/B	/L in meters	/H	number of reels
2G32.1000	/12	/1'200	/6	/3

All dimensions are in mm, unless otherwise stated.
Subject to change without notice.

**Clackband
made of Transformerboard T IV**

c2 G32-1 E

Edition 08.00	replace 08.99	Folder How to order
------------------	------------------	------------------------